



OPTIMA



best sprayer - top of quality
LT 1500 - LT 2000



Standard equipment

OPTIMA.1500	Tank lt. 1500 Rubber 10.0/75 – 15.3
OPTIMA.2000	Tank lt. 2000 Rubber 10.0/75 – 15.3

Technical data: tank's measures

	1500lt	2000lt
		
Altezza minima/ Min. height	136 cm	153 cm
Altezza standard/ Std. height	136 cm	153 cm
Larghezza/Width	148 cm	148 cm
Lunghezza/Lenght	250 cm	250 cm
Peso/Weight	295 kg	320 kg


Technical data: components



Potenza richiesta \geq	CV 75 - 55 KW
--------------------------	---------------



Ventola	Diametro 550mm 4100 giri/min 18.000 m ³ /hr
---------	--



Pompa a bassa pressione [optional]	Portata massima 135 lt/min Pressione massima 20 bar
---------------------------------------	--



Pompa centrifuga	Portata massima 200 lt/min Pressione massima 6 bar
------------------	---



Dosatori in acciaio INOX	0-1200 lt/min
--------------------------	---------------



Technical data: sprayer's measures

Modello	Altezza minima/ Min. height	Altezza standard/ Std. height	Larghezza/ Width	Lunghezza/ Lenght	Peso/Weight
Optima	145 cm	160 cm	152 cm	380 cm	500 kg

Optima: accessories on request ordered and installed at the origin

ACCESS.64	Universal joint cv 60-1000 mm
ACCESS.64.0M	Universal constant-velocity joint cv 60-1000 mm
ACCESS.15	Fill tube (filter and bottom valve)
ACCESS.42	Hydraulic movement of the upper distribution devices equipped with hydraulic lines with quick coupling
ACCESS.70.V4	4 solenoid valves V.M.A. to control liquid opening-closing
ACCESS.70.A4	4 solenoid valves ARAG to control liquid opening-closing
ACCESS.25	Electrical pressure regulator with remote control
ACCESS.EL	Electrostatic system for the positive charge of the treatment flow

Special devices

	BIG.T.SR55	2 guns and pair of stainless fans with hydraulic movement
	BIG.2C.2M4+4	2 guns 2 central hands 4+4 diffusers